

***YOUR PERFECT TRAVEL PARTNER
FOR EVERY JOURNEY***



SML ISUZU BUS RANGE

SCHOOL BUSES RANGE

- Safe, Comfortable & Economical School Buses



CNG VARIANT ALSO AVAILABLE



AVAILABLE IN AC

SML SCHOOL BUS

ECOMAX LR

S7 SCHOOL BUS

SPECIAL FEATURES

SML
ISUZU

SAFETY



School Bus Sign &
Yellow Exterior



Window Rail Guard



Emergency Exit Door



First Aid Kit &
Fire Extinguisher

COMFORT



Comfortable Seats
with Padded Arm Rest



Dedicated Racks for
School Bags




Back Seat Handles &
Bottle Hooks




Hat-Racks &
Grab Handles


ECONOMY



Highly Fuel
Efficient Engine



Box-type Chassis
for Longevity



Long Lasting
Robust Body



CNG Variant also
Available

STAFF AND TOURIST BUS RANGE

- For Staff Transportation
- Tours and Travels



CNG VARIANT ALSO AVAILABLE



AVAILABLE IN AC

ECOMAX

S7 STAFF BUS

SPECIAL FEATURES

SML
ISUZU



1025 mm wide, pushback & reclining seat for superior comfort



Spacious interiors with best in class gangway



USB mobile charging point



Wide hatracks provide extra room (Available with free flow AC variant)



Free flow AC with double blowers for uniform cooling



Sliding windows with guard rails



Ductable Air-conditioning option available



ECOMAX

S7 STAFF BUS

COMFORT



Comfortable Seats with Arm Rests



Low Foot step



LED saloon Lights

SAFETY



Emergency Exit



Peep Window for safe driving & better side view



Fire Extinguisher and First Aid Box

ECONOMY



Highly Fuel Efficient Engine



Long Lasting Robust Body



Adjustable Power Steering for less driver fatigue

STAFF AND TOURIST BUS RANGE

- ▶ For luxurious Staff Shuttle
- ▶ For luxurious Tours & Travels



Executive Bus

Executive^{LX} COACH

SPECIAL FEATURES



SENSE OF COMFORT AND LUXURY



Spacious Interiors with Best in Class Gangway & Hatracks



Pushback Seats with Padded Armrests & Footrests



Ergonomic Dashboard For Driving Comfort



Spacious Boot Suitable For Long Travels

SPECIAL FEATURES ABOUNDS



Individual AC Louvers & Reading Lamps



Mobile Charging Ports With Every Seat




On Board Entertainment with LCD Screen & Music System



Efficient, Timetested & Proven Engine

RESSURINGLY SAFE, LIKE NO ONE ELSE



Robust Structure For Safety



Anti Skid Flooring



Peep Window for Better Visibility on Sides



Driver Controlled Electro-pneumatic Door

SPECIFICATIONS: SCHOOL BUSES

ENGINE													
Description	BS-IV SLT4												
Displacement	3455 cc												
Engine Type	4-Cylinder In-line												
	Common Rail Direct Injection												
	Turbo-charger with Inter-cooler												
PERFORMANCE													
Engine Output (Max.)	75 kW ± 2% @ 2800 rpm												
Torque (Max.)	310 Nm @ 1500 ± 100 rpm												
TRANSMISSION													
Gear Box	Synchromesh Manual 5 - Forward, 1 - Reverse												
Clutch	Single Plate Dry Diaphragm type												
SUSPENSION	Semi-elliptical with Multi-leaf Springs												
VARIANT	SML School Bus								Ecomax LR	SML S7 Bus			
Wheel Base (mm)	Seating Capacity												
SEATING LAYOUT	2515	2815	2815	3335	3335	4240	4760	5100	2815	3335	4240	5100	
3 X 3	-	-	-	-	-	-	-	-	-	-	48+D	60+D	
3 X 2	21+D	24+D	24+D	26+D	31+D	41+D	46+D	51+D	-	30+D	42+D	52+D	
2 X 2	16+D	18+D	18+D	20+D	24+D	32+D	36+D	40+D	18+D	-	30+D	38+D	
2 X 1	-	-	-	-	-	-	-	-	13/12+D	-	-	-	
No. of Tyres	6+1	4+1	6+1	4+1	6+1	6+1	6+1	6+1		6+1	6+1	6+1	
Tyre Size	7.50X16-16PR			7.50X16-16PR/8.25X16PR			8.25X16-16PR		7.00 R x 16 - 12 PR	7.5 x 16 - 16 PR	8.25 x 16 - 16 PR		
Power Steering	Optional	Optional	Optional	Optional	Optional	Available	Available	Available	Available	Available	Available	Available	
Brakes	H*	H	H	H/A	H/A	H/A	H/A	A	H	H/A	A	A	

*H - Hydraulic Brakes, H/A - Hydraulic or Air optional, A - Air Brakes, Optional - Mechanical or Power Steering Option

Disclaimer: The specifications given in the table above may change without any prior notice, as per company policy of the continues improvement of its Products & Service.

SPECIFICATIONS: STAFF & TOURIST BUSES

ENGINE				
Description	BS-IV SLT4			
Displacement	3455 cc			
Engine Type	4-Cylinder In-line Common Rail Direct Injection Diesel Turbo-charger with Inter-cooler			
PERFORMANCE				
Engine Output (Max.)	75 kW \pm 2% @ 2800 rpm			
Torque (Max.)	310 Nm @ 1500 \pm 100 rpm			
TRANSMISSION				
Gear Box	Synchromesh Manual 5 - Forward & 1 - Reverse			
Clutch	Single Plate Dry Diaphragm type			
SUSPENSION	Semi-Elliptical Multiple Leaf Springs with hydraulic shock absorber			
	Ecomax	S7 Staff Bus		
Wheel Base (mm)	2815	3335	4240	5100
Gross Vehicle Weight (Max. Permissible) (kg)	4550	7000	7920	8800
	(2x1 High Back Reclining)	(2x2 High Head Rest Seats)		
Air Conditioned Bus (Driver's Partition in S7 only)	13 + 1 / 12 + 1 (Optional)	19 + 1 + 1	27 + 1 + 1	35 + 1 + 1
Non Air Conditioned Bus	13 + 1 / 12 + 1 (Maxicab)	22 + 1	30 + 1	38 + 1
No. of Tyres	4+1	6+1	6+1	6+1
Power Steering	Optional*	Optional	Available	Available
Brakes	Hyd**	Hyd / Air	Air	Air

** Hyd - Hydraulic Brakes, Air - Pneumatic Brakes, *Optional - Mechanical or Power Steering Option

Disclaimer: Above specifications may change without any prior notice, as per the company's policy of continuous improvement of its products/services.

TWIN DOOR BUSES ALSO AVAILABLE

SPECIFICATIONS: STAFF & TOURIST BUSES

ENGINE		
Model	SLT4, BS IV Compliant	
Type	Diesel Engine Common Rail Direct Injection Turbo-charged with Inter Cooler (In line 4 cylinders)	
Displacement	3455 cc	
Power (Max. Engine Output)	75 kW ± 2% at 2800 rpm	
Max. Torque	310 Nm at 1500 ± 100 rpm	
ELECTRICAL		
System Voltage	12 V	
Battery Rating (Voltage, Current)	12 V, 70 A/h	
STEERING		
Power Steering	yes	
Type	Recirculating Ball Type	
DRIVE TRAIN		
Clutch Type	Dry Single Plate	
Transmission	5 Forward + 1 Reverse	
SUSPENSION		
Type	Semi-Elliptical with Multi Leaf Springs	
Shock Absorbers	Hydraulic Double Acting & Telescopic Dampers (Front & Rear)	
BRAKES		
Service Brakes	Dual Circuit Vacuum Assisted Pneumatic	
Parking Brake	Mechanical Expanding Type on Rear Wheels	
Auto Slack Adjuster	Provided	
ABS	Provided	
TIRES		
Tire Size	6 + 1, 8.25 x 16 - 16 PR	
FUEL TANK		
Capacity	90 litres	
DIMENSIONS & SEATS	EXECUTIVE LX COACH	EXECUTIVE COACH
Wheel Base	4240 mm	2815 mm
Seats	18 + 1 + 1 Reclining Pushback 27 + 1 + 1 Semi Reclining Highback 29 + 1 + 1 Semi Reclining Highback	13 + 1 / 12 + 1 Reclining Pushback - -
Ground Clearance	206 mm	206 mm
Overall Length	8291 mm	5857 mm
Overall Width	2262 mm	2155 mm
Overall Height	3060 mm	3125 mm

EXCELLENT CHOICE

SML
ISUZU

TRUCK & BUSES



TRUCK RANGE

GVW from 5,000 kg to 12,000kg
Cargo Length - from 3.1m (11.5ft) to 6.6m (12ft)



BUS RANGE

School, Staff & Tourist Buses
Available in 18 to 52 No. of Seats

WHY CHOOSE SML?

- ◆ Wide and Far Reaching Network
- ◆ Excellent Service Support
- ◆ Trustworthy and be assured that your vehicle is in safe hands when it comes to service
- ◆ Easy Availability of Spares
- ◆ Easy finance available from all leading Banks and financial leading initiations

WARRANTY*

- ◆ SML /S7 (School/Staff) /Executive LX
 - Engine: 2 years unlimited km run
 - Vehicle: 1 year on unlimited km run
- ◆ ecoMax / WV26 (4 Tyres) Models / Executive Coach:
 - Engine: 3 years or 3 Lac km run whichever is earlier'
 - Vehicle: 1 year on unlimited km run

ALWAYS USE GENUINE SML ISUZU SPARES



Authorized Distributor of SML ISUZU for Nepal

📍 Bhagwati Bahal Marg, Naxal, Kathmandu, Nepal

☎ Tel: 01 4444107, 4440106

✉ E-mail: care@sml-gfi.com

